



## OS67

Part: OCS6700B, OCS6700W  
 Woofer: 4 x 8" Glass Fiber, 2 Passive Radiator  
 Tweeter: 1" Aluminum  
 Power RMS: 50 Watts  
 Power peak: 150 Watts  
 Frequency Response: 52Hz-20kHz  
 Impedance: 6 ohm  
 Enclosure: HDPE  
 Grille: Aluminum  
 Dimensions: 3 3/16 x 6 1 1/16 x 13 1/8"  
 (182 x 172 x 334mm)  
**MSRP: \$400/EA**



## OS65DT

Part: OCS6500DTB, OCS6500DTW  
 Woofer: 4 x 8" IMG, 2 Passive Radiator  
 Tweeter: 1" Dual Aluminum  
 Power RMS: 50 Watts  
 Power peak: 150 Watts  
 Frequency Response: 58Hz-20kHz  
 Impedance: 6 ohm  
 Enclosure: HDPE  
 Grille: Aluminum  
 Dimensions: 3 3/16 x 6 1 1/16 x 13 1/8"  
 (182 x 172 x 334mm)  
**MSRP: \$550/EA**



## OS65

Part: OCS6500B, OCS6500W  
 Woofer: 4 x 8" IMG, 2 Passive Radiator  
 Tweeter: 1" Aluminum  
 Power RMS: 50 Watts  
 Power peak: 150 Watts  
 Frequency Response: 58Hz-20kHz  
 Impedance: 6 ohm  
 Enclosure: HDPE  
 Grille: Aluminum  
 Dimensions: 3 3/16 x 6 1 1/16 x 13 1/8"  
 (182 x 172 x 334mm)  
**MSRP: \$345/EA**



## OS57

Part: OCS5700B, OCS5700W  
 Woofer: 5 1/4" Glass Fiber  
 Tweeter: 3/4" Aluminum  
 Power RMS: 50 Watts  
 Power peak: 125 Watts  
 Frequency Response: 52Hz-20kHz  
 Impedance: 6 ohm  
 Enclosure: HDPE  
 Grille: Aluminum  
 Dimensions: 3 3/16 x 6 1 1/16 x 13 1/8"  
 (182 x 172 x 334mm)  
**MSRP: \$260/EA**



## OS55DT

Part: OCS5500DTB, OCS5500DTW  
 Woofer: 5 1/4" IMG  
 Tweeter: Dual 3/4" Aluminum  
 Power RMS: 50 Watts  
 Power peak: 125 Watts  
 Frequency Response: 63Hz-20kHz  
 Impedance: 6 ohm  
 Enclosure: HDPE  
 Grille: Aluminum  
 Dimensions: 3 3/16 x 6 1 1/16 x 10 1 3/32"  
 (182 x 172 x 266mm)  
**MSRP: \$375/EA**



## OS55

Part: OCS5500B, OCS5500W  
 Woofer: 5 1/4" IMG  
 Tweeter: 3/4" Aluminum  
 Power RMS: 50 Watts  
 Power peak: 125 Watts  
 Frequency Response: 63Hz-20kHz  
 Impedance: 6 ohm  
 Enclosure: HDPE  
 Grille: Aluminum  
 Dimensions: 3 3/16 x 6 1 1/16 x 10 1 3/32"  
 (182 x 172 x 266mm)  
**MSRP: \$235/EA**